

Tik

bollard light



Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Installation	Page 3
5. Photometric Data and Technical Information	Page 3
6. Ordering codes	Page 4
7. Certifications & standards	Page 5
8. Maintenance & Cleaning	Page 5

Versions



TIK_4096X
Page 4



TIK_4097X
Page 4

Tik

bollard light

1. Product overview

Metallic outdoor bollard light with a PMMA lens diffuser (60° beam angle) and integrated LED, providing direct light.

The cylindrical tube encloses the light source and is non-adjustable.

Model TIK_4096X directs the light downward.

Model TIK_4097X directs the light upward.

Built-in driver for direct mains connection. Surface-mounted on a solid base.

A double-layer coating ensures high resistance.



2. Finishes and Materials



88 Grey Stone

96 Anthracite

89 Pale Green

3. Light Source & Dimming

Lamping

LED 6,2W (2700K / Ang. 60° / >90 CRI / 350mA) 230V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°.

*Integrated LED module (included).

Dimming options:

Standard: TRIAC

Optional: DALI

4. Installation

Built-in driver for direct mains connection

Surface-mounted on a solid base (concrete or similar).
Not suitable for installation on soil or grass.



60° beam angle


Acrylic optic. It provides diffuse, uniform illumination and is visible as a decorative light line when viewed from the side.



5. Photometric Data and Technical Information

Photometric data corresponds to the output of each individual lamp.
Access to photometric files in download area.

2D / 3D / BIM Files available. Access to files in download area here.



6. Ordering Codes

Lamping 4096X

LED 6,2W (2700K / Ang. 60° / >90 CRI / 350mA)

230V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°

DIM: TRIAC (Optional DALI)

Finishes:

88 Grey Stone

89 Pale Green

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4096X IP65 	Bollard light. Hard wired (no plug). Surface mounted on a solid base.	Outdoor	Grey Stone	TIK_4096X_88W
		Outdoor	Pale Green	TIK_4096X_89W
			Anthracite	TIK_4096X_96W

Lamping 4097X

LED 6,2W (2700K / Ang. 60° / >90 CRI / 350mA)

230V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°

DIM: TRIAC (Optional DALI)

Finishes:

88 Grey Stone


89 Pale Green

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4097X IP65 	Bollard light. Hard wired (no plug). Surface mounted on a solid base.	Outdoor	Grey Stone	TIK_4097X_88W
		Outdoor	Pale Green	TIK_4097X_89W
			Anthracite	TIK_4097X_96W

7. Certifications & Standards



Warranty: 2 years
100% made in Spain

8. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.