




Table of contents

|                                               |        |
|-----------------------------------------------|--------|
| 1. Product overview                           | Page 2 |
| 2. Finishes and materials                     | Page 2 |
| 3. Light Source & dimming                     | Page 2 |
| 4. Installation                               | Page 3 |
| 5. Photometric Data and Technical Information | Page 3 |
| 6. Ordering codes                             | Page 4 |
| 7. Certifications & standards                 | Page 5 |
| 8. Maintenance & Cleaning                     | Page 5 |

Versions



TIK\_4091X (Outdoor version)  
Page 4



TIK\_4091 (Indoor version)  
Page 4

# Tik

wall light

## 1. Product overview

Metallic wall-mounted lamp for accent or ambient lighting, providing both direct and indirect illumination.

Available in indoor and outdoor versions. The outdoor model features a PMMA lens diffuser with a 60° beam angle, while the indoor version includes an embedded aluminium optic lens with a 30° beam angle. Both models incorporate an integrated dimmable LED, projecting light upward and downward through a fixed cylindrical tube enclosing the light source.

Outdoor version: The remote driver must be installed in an IP65-rated box or indoors. Maximum cable length between driver and lamp: 17 meters. A double-layer coating ensures high resistance.



## 2. Finishes and Materials



88 Grey Stone (Outdoor and Indoor)  
96 Anthracite (Outdoor and Indoor)  
89 Pale Green (Outdoor Only)  
61 Satin Gold (Indoor Only)

## 3. Light Source & Dimming

### Lamping per head (Outdoor):

LED 2x3W (2700K / Ang. 60° / >90 CRI / 24V)  
230V / Typ 2x300 lumens

Optic lens: (PMMA) lens diffuser 60°.

\*Integrated LED module (included).

### Dimming options:

Standard: TRIAC

Optional: DALI

### Lamping per head (Indoor):

LED 2x3W (2700K / Ang. 30° / >90 CRI / 300mA)  
230V / Typ 2x350 lumens

Optic lens: embedded aluminium optic lens 30°.

\*Integrated LED module (included).

### Dimming options:

Optional: DALI

## 4. Installation

### Outdoor

Recessed canopy with remote driver



Remote driver must be placed in IP 65 box or inside the home. Maximum distance from the driver to the lamps 17 meters.

### Indoor

Surface canopy



### 60° beam angle

Acrylic optic. It provides diffuse, uniform illumination and is visible as a decorative light line when viewed from the side.



### 30° beam angle

Architectural optic conceals the LED source within a conical aluminium lens. It projects light exclusively downward (no lateral emission).




## 5. Photometric Data and Technical Information

Photometric data corresponds to the output of each individual lamp. Access to photometric files in download area.

2D / 3D / BIM Files available. Access to files in download area here.

TIK\_4091X



## 6. Ordering Codes

### Lamping 4091X (Outdoor version)

LED 2x3W (2700K / Ang. 60° / >90 CRI / 24V)

230V / Typ 2x300 lumens

**Optic lens:** (PMMA) lens diffuser 60°.

**DIM:** TRIAC (Optional DALI)

### Finishes:

88 Grey Stone

89 Pale Green

96 Anthracite



| Drawing                   | Mounting                | Setting | Finish Body | Ordering Code |
|---------------------------|-------------------------|---------|-------------|---------------|
| TIK_4091X<br>IP65<br><br> | Recessed, remote driver | Outdoor | Grey Stone  | TIK_4091X_88W |
|                           |                         | Outdoor | Pale Green  | TIK_4091X_89W |
|                           |                         |         | Anthracite  | TIK_4091X_96W |

### Lamping 4091 (Indoor version)

LED 2x3W (2700K / Ang. 30° / >90 CRI / 300mA)

230V / Typ 2x350 lumens

**Optic lens:** embedded aluminium optic lens 30

**DIM:** Optional DALI

### Finishes:

61 Satin Gold

88 Grey Stone

96 Anthracite



| Drawing                  | Mounting                      | Setting | Finish Body | Ordering Code |
|--------------------------|-------------------------------|---------|-------------|---------------|
| TIK_4091<br>IP20<br><br> | Wall light<br>Surface mounted | Indoor  | Satin Gold  | TIK_4091_61W  |
|                          |                               | Indoor  | Grey Stone  | TIK_4091_88W  |
|                          |                               |         | Anthracite  | TIK_4091_96W  |

## 7. Certifications & Standards

TIK\_4091X       850° 

TIK\_4091        

Warranty: 2 years

100% made in Spain

## 8. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.