

Tik

wall light




Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Installation	Page 3
5. Ordering codes	Page 4
6. Certifications & standards	Page 5
7. Maintenance & Cleaning	Page 5

Versions



TIK_4090X (Outdoor version)
Page 4



TIK_4090 (Indoor version)
Page 4

Tik

wall light

1. Product overview

Metallic wall-mounted lamp for accent or ambient lighting, available in indoor and outdoor versions.

The outdoor version features a PMMA diffuser with a 60° beam angle, while the indoor version includes an embedded aluminium optic lens with a 30° beam angle. Both models incorporate a dimmable integrated LED, providing direct light through a fixed cylindrical tube enclosing the light source.

Outdoor version: The remote driver must be installed in an IP65-rated box or indoors. Maximum cable length between driver and lamp: 17 meters. Double-layer coating ensures high resistance.



2. Finishes and Materials



88 Grey Stone (Outdoor and Indoor)
96 Anthracite (Outdoor and Indoor)
89 Pale Green (Outdoor Only)
61 Satin Gold (Indoor Only)

3. Light Source & Dimming

Lamping (Outdoor):

LED 3W (2700K / Ang. 60° / >90 CRI / 24V)
100-240V / Typ 300 lumens
Optic lens: (PMMA) lens diffuser 60°.
*Integrated LED module (included).

Dimming options:

Standard: TRIAC
Optional: DALI

Lamping (Indoor):

LED 6,2W (2700K / Ang. 30° / >90 CRI / 300mA)
230V / Typ 652 lumens
Optic lens: embedded aluminium optic lens 30°.
*Integrated LED module (included).

Dimming options:

Optional: DALI

4. Installation

Outdoor

Recessed canopy with remote driver



Remote driver must be placed in IP 65 box or inside the home. Maximum distance from the driver to the lamps 17 meters.

Indoor

Surface canopy



60° beam angle

Acrylic optic. It provides diffuse, uniform illumination and is visible as a decorative light line when viewed from the side.



30° beam angle

Architectural optic conceals the LED source within a conical aluminium lens. It projects light exclusively downward (no lateral emission).



5. Ordering Codes

Lamping 4090X (Outdoor version)

LED 3W (2700K / Ang. 60° / >90 CRI / 24V)

100-240V / Typ 300 lumens

Optic lens: (PMMA) lens diffuser 60°.

DIM: TRIAC (Optional DALI)


Finishes:

88 Grey Stone

89 Pale Green

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4090X IP65 	Recessed, remote driver	Outdoor	Grey Stone	TIK_4090X_88W
		Outdoor	Pale Green	TIK_4090X_89W
			Anthracite	TIK_4090X_96W

Lamping 4090 (Indoor version)

LED 6,2W (2700K / Ang. 30° / >90 CRI / 300mA)

230V / Typ 652 lumens

Optic lens: embedded aluminium optic lens 30

DIM: Optional DALI


Finishes:

61 Satin Gold

88 Grey Stone

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4090 IP20 	Wall lamp Surface mounted	Indoor	Satin Gold	TIK_4090_61W
		Indoor	Grey Stone	TIK_4090_88W
			Anthracite	TIK_4090_96W

6. Certifications & Standards

TIK_4090X     

TIK_4090     

Warranty: 2 years

100% made in Spain

7. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.